



SENTRON, fuse switch disconnecter 3NP1, 1-pole, NH1, 250 A, for assembly and installation on mounting plate, Box terminal, cover level 70mm

Model	
product brand name	SENTRON
product designation	3NP1 fuse switch disconnecter
design of the product	cover level 70 mm
design of the safety monitoring	Without
design of the actuating element	Cover handle
design of the load switch / strip form	No
type of the driving mechanism / motor drive	No
General technical data	
number of poles	1
type of device	For assembly and installation on mounting plate
size of disconnecting link	1 and 0
size of fuse link	NH0, NH1
let-through current / with closed switch / maximum permissible	32 kA
mechanical service life (switching cycles) / typical	1 600
power factor	
• at AC-22 B	0.65
• at AC-23 B	0.35
• with capacitive load	-0.25
fuse system	LV HRC fuse
degree of pollution	3
Voltage	
insulation voltage	
• rated value	690 V
• with degree of pollution 3 / at AC / rated value	690 V
• with degree of pollution 2 / at AC / rated value	1 000 V
power factor / at AC-21 B	0.95
surge voltage resistance / rated value	8 kV
operating voltage	
• at AC / rated value / maximum	240 V
• at DC / rated value	120 V
• at DC / rated value / maximum	120 V
Protection class	
protection class IP	
• with closed switch / with cover or cable lug cover	IP40
• with closed switch / without cover or cable lug cover	IP30
• on the front	IP40

• open	IP20
Dissipation	
power loss [W]	
• with conventional rated thermal current / without fuse / per pole	8 W
• with conventional rated thermal current / without fuse / per device	8 W
• for rated value of the current / at AC / in hot operating state / per pole	31 W
• of the fuse / per fuse / maximum	23 W
Current	
operational current	
• at 35 °C / rated value	250 A
• at 40 °C / rated value	245 A
• at 45 °C / rated value	240 A
• at 50 °C / rated value	233 A
• at 55 °C / rated value	233 A
• at AC / rated value	250 A
• at AC-23 B / at 240 V / rated value	250 A
• at AC-22 B / at 240 V / rated value	250 A
• at AC-21 B / at 240 V / rated value	250 A
• at DC-23 B / at 120 V / rated value	200 A
• at DC-22 B / at 120 V / rated value	250 A
• at DC-21 B / at 120 V / rated value	250 A
let-through current / with high-speed activation / maximum permissible	25 kA
Main circuit	
operational current	
• rated value	250 A
• with capacitive load / at 400 V / rated value	72 A
• with capacitive load / at 500 V / rated value	55 A
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	0
number of NC contacts / for auxiliary contacts	0
number of NO contacts / for auxiliary contacts	0
Suitability	
suitability for use	
• main switch	No
• switch disconnecter	Yes
• EMERGENCY OFF switch	No
• safety switch	Yes
• maintenance/repair switch	Yes
Product details	
product feature / interlock	Yes
• product component / trip indicator	No
• product function / phase failure monitoring	No
• product component / undervoltage release	No
• product component / undervoltage release with leading contact	No
product feature / sealable	Yes
product extension / auxiliary switch	Yes
product extension / optional	
• locking capability	Yes
• motor drive	No
• phase failure monitoring	No
• fuse monitoring	Yes
• voltage trigger	No
• overvoltage protection monitoring	No

Product function			
product function			
<ul style="list-style-type: none"> • fuse monitoring 	No		
<ul style="list-style-type: none"> • overvoltage protection monitoring 	No		
Short circuit			
conditional short-circuit current (I _q)			
<ul style="list-style-type: none"> • rated value 	80 kA		
<ul style="list-style-type: none"> • at AC / at 240 V / with high-speed activation / rated value 	80 kA		
<ul style="list-style-type: none"> • with closed switch / at AC / at 240 V / rated value 	120 kA		
Connections			
arrangement of electrical connectors / for main current circuit	other		
connectable conductor cross-section / for main contacts			
<ul style="list-style-type: none"> • solid or stranded / minimum 	70 mm ²		
<ul style="list-style-type: none"> • solid or stranded / maximum 	185 mm ²		
<ul style="list-style-type: none"> • finely stranded / with core end processing / minimum 	70 mm ²		
<ul style="list-style-type: none"> • finely stranded / with core end processing / maximum 	120 mm ²		
<ul style="list-style-type: none"> • stranded / minimum 	70 mm ²		
<ul style="list-style-type: none"> • stranded / maximum 	185 mm ²		
tightening torque / with screw-type terminals			
<ul style="list-style-type: none"> • minimum 	10 N·m		
<ul style="list-style-type: none"> • maximum 	10 N·m		
type of connectable conductor cross-sections / of the laminated conductors / maximum	20 x 10 mm		
type of connection technology	Box terminal		
type of electrical connection / for main current circuit	box terminal		
Mechanical Design			
height	306 mm		
width	69.7 mm		
depth	116 mm		
fastening method	mounting plate		
fastening method			
<ul style="list-style-type: none"> • floor mounting 	Yes		
<ul style="list-style-type: none"> • 4-hole front mounting 	No		
<ul style="list-style-type: none"> • front mounting with central attachment 	No		
<ul style="list-style-type: none"> • rail mounting 	No		
mounting position	horizontal/vertical		
Environmental conditions			
ambient temperature / during operation			
<ul style="list-style-type: none"> • minimum 	-25 °C		
<ul style="list-style-type: none"> • maximum 	55 °C		
ambient temperature / during storage			
<ul style="list-style-type: none"> • minimum 	-50 °C		
<ul style="list-style-type: none"> • maximum 	80 °C		
General Product Approval	Declaration of Conformity	Test Certificates	Marine / Shipping

[Miscellaneous](#)



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



other

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3NP1141-1DA20>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NP1141-1DA20>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3NP1141-1DA20

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





